

Bronz-Glow® Product Data

“Component Coat”

Flexible, Durable, Single Component Coating for HVAC/R Components

CORROSION PROTECTION FROM: Environments containing heavy moisture concentrations, salt air/spray, acid rain, chlorine, muriatic acid fumes, ammonia, H₂S fumes, sulfuric acid fumes, methane fumes, most other aggressive acids and alkali solutions and UV light by natural or artificial means.

COATING RECOMMENDATIONS: Corrosion protection for virtually any type of HVAC/R components including; TXV Valves, filter driers, copper tubing, fan blades, blower wheels, tubing insulation= fibrous and high density, ball valves, and much more. Full protection in environments such as; waste- water treatment plants, paper mills, any type of coastal installation, food processing facilities, refineries, off shore facilities, chemical plants, medical facilities, pharmaceutical plants, steel mills, mining facilities etc.

BENEFITS:

- Provides corrosion resistance across the entire pH Range (1.0 to 14.0)
- Impermeable to moisture in immersion service when applied 12 to 15 dft (dry film thickness)
- Single component convenience and savings
- Applicable to virtually any type of surface
- Safe for all non-food contact surfaces
- Easy to apply by aerosol spray
- Bonds to metals, wood, concrete, glass, plastics, fiberglass etc.
- Contains a 10-year Florida sun UV inhibitor

DESCRIPTION: This unique air-dry coating provides durable surface protection in harsh environments where other coatings and paints fail. Dries to touch in minutes and fully cures in 24 hours. Formulated with a synthetic resin base, “Component Coat” becomes impermeable to moisture at 12-15 mils dry thickness. “Component Coat” provides virtually total moisture resistance from harsh alkaline and acidic solutions at 12-15 mils thick (Immersion Service). Standard HVAC/R cabinet coating applications are applied at 3-5 mils for general corrosion protection.

COATING CHARACTERISTICS:

Solids: (wt) 28%	Stone Abrasion: Excellent (ASTM D-3170)
Tensile: 2,500 psi (ASTM D-638)	Weather ability: Excellent (ASTM G-53) 7-10 yrs.
Permeability: 03 grains / sq. ft. /hr	Finish: Semi-gloss
Temperature use range: -30 to 220° F	Viscosity range: 85 – 95 K.V. @ 77 degrees F.
Shelf life: 1 year @ 77° F	Elongation: 230% (ASTM D-2370-82)
VOC lbs. per gallon: 4.8 - 5.1	Cut Resistance: Very Good (ASTM D-1044)
Salt Spray 2,000 hrs (ASTM B-117.85)	Dielectric Strength: 1.400 / mil (ASTM D-149)
Gas Chromatography Test (FID) No evidence of residual solvent vapors	

AVAILABLE COLOR: Platinum, special colors available upon request.

Packaging: Aerosol Cans @ 12oz each, 12 per case.

Bronz-Glow, Husky Logo is Registered Trademark of Bronz-Glow Holdings, St. Augustine, FL.

Husky "Component Coat" Technical Data

Surface Preparation:

- Remove all traces of oil, grease, rust, dirt and dust
- Sandblast or roughen surfaces to improve adhesion
- Remove all loosened residue, wipe or rinse clean
- Prime with Husky Green Fin Primer

Provide ventilation and use approved personal safety protection when handling or applying coatings.

For more detailed information, call, email, or visit our web site

Distributed by Bronz-Glow Technologies, Inc.

175 Bronz-Glow Way

St. Augustine, FL 32095

Ph: (904) 825-0175 or Fax: 904-825-0122

E-mail: Customerserv@bronz-glow.com or www.bronz-glow.com

Conditions of use: "The information, data contained herein, is believed to be reliable and based on our knowledge & experience; however, seller does not guarantee the result obtained by buyer. Seller hereby expressly disclaims any implied warranty, of merchantability for fitness for a particular purpose and / or any other warranty expressed or implied as to any and all products and / or suggestions described herein, whether such are used alone or in conjunction with other materials. Buyer must make its own determination of suitability of any products for its use and the completeness of any information. In no event shall Bronz-Glow technologies, Inc. Holdings Trust be liable for consequential or incidental damages."

