



MATERIAL SAFETY DATA SHEET

Page 1 of 6
"Green Fin" Protector
Part No. B62727CT Aerosol
Revision 2 ~ June 6, 2005

EMERGENCY OVERVIEW

CONTENTS **EXTREMELY FLAMMABLE** AND **UNDER PRESSURE**. STORE BELOW 120°F, OUT OF SUNLIGHT, AND AWAY FROM HEAT SOURCES. DO NOT PUNCTURE OR INCINERATE. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

SUPPLIER: Bronz-Glow Technologies, Inc.
175 Bronz-Glow Way, St. Augustine, FL 32095 USA

INFORMATION: 904-825-0175
24hr EMERGENCY: 800-424-9300 Chemtrec USA
703-527-3887 Chemtrec International

PRODUCT IDENTIFIER: B6272CT
PRODUCT DESCRIPTION: Husky® "Green Fin" Coil Protector
PRODUCT USE: Protects against seacoast and other corrosive atmospheres

PRODUCT TYPE: Aerosol
CAS NUMBER: Mixture
EMAIL: msds@chem-pak.com
WEBSITE: http://www.chem-pak.com

REVISION NUMBER: 2
REVISION DATE: June 6, 2005
PRINT DATE: June 6, 2005
PREPARED BY: Safety & Environmental Manager

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	OSHA PEL	NIOSH REL	ACGIH PEL	IDLH	% WT
Liquefied Petroleum Gas	068476-85-7	1000 ppm	1000 ppm	1000 ppm	2000 ppm	20-30
VM&P Naphtha	064742-89-8	N/E	N/E	N/E	N/E	20-30
Methyl Ethyl Ketone	000078-93-3	200 ppm	200 ppm	200 ppm	3000 ppm	10-20
n-Hexane	000110-54-3	500 ppm	50 ppm	50 ppm	1100 ppm	10-20
Toluene	000108-88-3	200 ppm	100 ppm	50 ppm	500 ppm	< 10

See Section 11 for LD50 and LC50 Species/Route Information.
See Section 15 for Symbol Letters and R Phases.

SECTION 3 HAZARD IDENTIFICATION

ROUTES OF ENTRY:

Skin Contact	<input checked="" type="checkbox"/>	Skin Absorption	<input checked="" type="checkbox"/>	Eye Contact	<input checked="" type="checkbox"/>	Inhalation	<input checked="" type="checkbox"/>	Ingestion	<input type="checkbox"/>
--------------	-------------------------------------	-----------------	-------------------------------------	-------------	-------------------------------------	------------	-------------------------------------	-----------	--------------------------

EFFECTS OF ACUTE EXPOSURE

EYE: Liquid contact may cause pain along with moderate eye irritation.

SKIN: Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.

INGESTION: Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.

INHALATION: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnoea are also possible.

OTHER HEALTH HAZARD DATA

EFFECTS OF CHRONIC EXPOSURE: Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.



MATERIAL SAFETY DATA SHEET

Toluene: Reports of chronic poisoning describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect a developing fetus.

n-Hexane is toxic to the peripheral nerves, characterized by numbness, tingling, or pain in the extremities, progressively worsening of neuromuscular moto coordination (polyneuritis or polyneuropathy), and even partial paralysis.

MEDICAL CONDITIONS AGGRAVATED: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

PRIMARY HAZARDS: Sensory Irritation (methyl ethyl ketone), Narcosis (toluene), Neuropathy (n-hexane)

CARCINOGEN DATA: None of the ingredients are considered carcinogenic by OSHA, IARC, NTP, NIOSH or ACGIH.

CALIFORNIA PROP-65 WARNING: This product contains substances known to the State of California to cause birth defects, and/or other reproductive harm.

TARGET ORGANS: Eyes, skin, respiratory system, central nervous system, reproductive system, liver, kidneys, peripheral nervous system

OSHA HAZARD CLASSIFICATIONS

HEALTH HAZARD CLASSIFICATION				PHYSICAL HAZARD CLASSIFICATION					
Irritant	<input checked="" type="checkbox"/>	Sensitizer	<input checked="" type="checkbox"/>	Combustible	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Pyrophoric	<input type="checkbox"/>
Toxic	<input checked="" type="checkbox"/>	Highly Toxic	<input type="checkbox"/>	Flammable	<input checked="" type="checkbox"/>	Oxidizer	<input type="checkbox"/>	Water Reactive	<input type="checkbox"/>
Corrosive	<input type="checkbox"/>	Carcinogenic	<input type="checkbox"/>	Compressed Gas	<input checked="" type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>	Unstable	<input type="checkbox"/>

SECTION 4 FIRST AID MEASURES

INGESTION: Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.

SKIN: Remove with soap and water. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.

EYE: Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

NOTES TO PHYSICIAN: Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias (irregular beating) in persons exposed to high concentrations of n-Hexane. If used, monitor heart activity closely.

SECTION 5 FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY: Heat, sparks, flame, red hot metal

SUITABLE MEANS OF EXTINGUISHION: Water, CO₂, dry chemical, or universal aqueous film forming foam.

UNSUITABLE EXTINGUISHING MEDIA: N/Av

FLASH POINT AND METHOD OF DETERMINATION: Propellant < 0 F, Tagged Closed Cup

FLAMMABLE LIMITS: Lower (LEL): 1.8% @ 25 C Upper (UEL): 9.5% @ 25 C

AUTOIGNITION TEMPERATURE: N/Av

HAZARDOUS COMBUSTION PRODUCTS: Oxides of Carbon (CO, CO₂), smoke, and vapors as products of incomplete combustion.

EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT: N/Av

EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE: N/Av

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.

SPECIAL FIRE AND EXPLOSION HAZARDS: Contents extremely flammable and under pressure.

SECTION 6 ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill.

SPILL CLEANUP: Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

SPECIAL INSTRUCTIONS: Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilate provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.

REPORTING REQUIREMENTS: Spills due to the rupture of a single aerosol can are generally below any regulatory reporting requirements. However, if larger spills somehow result, the reporting requirements of all governing agencies should be observed.



MATERIAL SAFETY DATA SHEET

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY:

INGREDIENT	FISH LC50	DAPHNIA EC50	ALGAL IC50	BACTERIAL EC50
Liquefied Petroleum Gas	N/Av	N/Av	N/Av	N/Av
VM&P Naphtha	N/Av	N/Av	N/Av	N/Av
Methyl Ethyl Ketone	3220 mg/l /96 hr	5061 mg/l /48 hr	>4300 mg/l /7 day	1150 mg/l /16 hr
n-Hexane	4 mg/l /24 hr	2.1 mg/l /48 hr	1079 mg/l /96 hr	N/Av
Toluene	13 mg/l /96 hr	11 mg/l /48 hr	12 mg/l /72 hr	20 mg/l /30 min

MOBILITY: N/Av

PERSISTANCE: N/Av

DEGRADIBILITY: N/Av

BIOACCUMULATION: N/Av

OTHER ECOLOGIC DATA: Do not allow to enter waters, waste water, or soil. Toluene is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

EFFECT ON OZONE LAYER: ... This product does not contain any ozone depleting ingredients.

SECTION 13 DISPOSAL CONSIDERATIONS

Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

SECTION 14 TRANSPORTATION INFORMATION

DOT SHIPPING INFORMATION (United States)

PROPER SHIPPING NAME: . Consumer Commodity

HAZARD CLASS: ORM-D

PACKAGING GROUP: None

UN or ID NUMBER: None

TDG SHIPPING INFORMATION (Canada)

PROPER SHIPPING NAME: . Aerosols, Flammable Ltd Qty

HAZARD CLASS: 2.1

PACKAGING GROUP: -

UN or ID NUMBER: UN1950

IMDG SHIPPING INFORMATION (International Ocean)

PROPER SHIPPING NAME: . Aerosols, Limited Quantity

CLASS: 2

PACKAGING GROUP: -

SUBSIDIARY RISK(S): -

UN or ID NUMBER: UN1950

PACKING INSTRUCTIONS: . P003

EmS NO.: F-D, S-U

STOWAGE: Category A

MFAG NO.: 620

ICAO/IATA SHIPPING INFORMATION (International Air)

PROPER SHIPPING NAME: Consumer Commodity

HAZARD CLASS: 9

PACKAGING GROUP: None

UN or ID NUMBER: ID8000

ADR SHIPPING INFORMATION (European Union)

PROPER SHIPPING NAME: Aerosols, Limited Quantity

ADR CLASS: 2

PACKAGING GROUP: -

UN or ID NUMBER: UN1950

CLASSIFICATION CODE: . LQ1

NMFC DESCRIPTION (United States)

ITEM DESCRIPTION: Compounds, Rust Preventing

ITEM NO.: 50234 Sub 3

CLASS: 65

NORTH AMERICAN EMERGENCY RESPONSE GUIDE

ID NUMBER: 8000

GUIDE NUMBER: 171



MATERIAL SAFETY DATA SHEET

Page 5 of 6
 "Green Fin" Protector
 Part No. B62727CT Aerosol
 Revision 2 ~ June 6, 2005

SECTION 15 REGULATORY INFORMATION

UNITED STATES - FEDERAL:

INGREDIENT	CAS NO	TSCA	RCRA	CERCLA	SARA 313	CAA	CWA
Liquefied Petroleum Gas	68476-85-7	T	-	-	-	-	-
VM&P Naphtha	64742-89-8	T	-	-	-	-	-
Methyl Ethyl Ketone	78-93-3	T	U159	5000#	12.3 %	XOV	-
n-Hexane	110-54-3	T	-	5000#	12.0 %	XOV	-
Toluene	108-88-3	T	U220	1000#	9.6 %	XOV	1000#

UNITED STATES - STATES:

INGREDIENT	CA	DE	FL	MA	PA	MN	NJ	NY	WA
Liquefied Petroleum Gas	-	-	-	-	-	-	-	-	-
VM&P Naphtha	-	-	-	-	-	-	-	-	-
Methyl Ethyl Ketone	-	T	T	2,4,5,6 F8 F9	E	ANO	T	T	T
n-Hexane	-	T	T	2,4,5,6	-	ANO	T	T	T
Toluene	D	-	T	2,4,5,6 F7 F8 F9	E	ANO	T	T	T

CANADA:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

All of the components in this product are listed on the Domestic Substances List (DSL).

WHMIS Classification: A, B5, D2A, D2B


EUROPEAN UNION:

INGREDIENT	EINECS	SYMBOL	RISK PHRASES	SAFETY PHRASES
Liquefied Petroleum Gas	270-704-2	F+	12	9-16-33
VM&P Naphtha	265-192-2	Xn	65	23-24-62
Methyl Ethyl Ketone	201-159-0	F, Xi	11-36-66-67	2-9-16
n-Hexane	203-777-6	F, Xi, Xn, N	11-38-48/20-51/53-62-65-67	9-16-29-33-36/37-61-62
Toluene	203-625-9	F, Xn	11	16-25-29-33

SECTION 16 OTHER INFORMATION



Canadian Hazard Symbols



European Hazard Symbols

HMIS and NFPA RATINGS:

	HEALTH	FLAMMABILITY	REACTIVITY	SPECIAL
HMIS RATING	2	4	0	B
NFPA RATING	2	4	0	-



MATERIAL SAFETY DATA SHEET

Page 6 of 6
"Green Fin" Protector
Part No. B62727CT Aerosol
Revision 2 ~ June 6, 2005

R and S PHASES (European Union):

CODE	RISK or SAFETY PHRASE
R12	<i>Extremely Flammable</i>
R36	<i>Irritating to the eyes</i>
R48/20	<i>Harmful: danger of serious damage to health by prolonged exposure through inhalation</i>
R51/53	<i>Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment</i>
R62	<i>Possible risk of impaired fertility</i>
R65	<i>Harmful: may cause lung damage if swallowed</i>
R66	<i>Repeated exposure may cause skin dryness or cracking</i>
R67	<i>Vapours may cause drowsiness and dizziness</i>
S2	<i>Keep out of the reach of children</i>
S9	<i>Keep container tightly closed</i>
S16	<i>Keep away from sources of ignition – No smoking</i>
S23	<i>Do not breathe vapours</i>
S24/25	<i>Avoid contact with skin and eyes</i>
S29	<i>Do not empty into drains</i>
S33	<i>Take precautionary measures against static discharge</i>
S36/37	<i>Wear suitable protective clothing and gloves</i>
S61	<i>Avoid release to the environment</i>
S62	<i>If swallowed do not induce vomiting: seek medical advise immediately</i>

DISCLAIMER OF LIABILITY:

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular purpose.

REVISIONS:

Revision 1 - 03/15/2005 Original
Revision 2 - 06/06/2005 Updated 25hr Emergency Contact Info