

Product Data Sheet

Husky® Coil Coat Black

Tough, Flexible Coating for Fin Tube and Coaxial Coils Doesn't Crack, Chip or Flake and has Minimal Effect on Heat Transfer

Coating Characteristics:

Solids: (wt) 24%

Tensile: 3,740 psi (ASTM D-638)

Finish: semi-gloss

Shelf Life: 1 + yrs @ 77° F (25° C) unopened

Elongation: 430 % (ASTM D-2370) Durometer: shore A 70 (ASTM D-2240)

Viscosity Range: 80 – 100 K.U. @ 77° F (+/- 2°F)

Dielectric: 1,400 v/mil (ASTM D-149)

Stone Abrasion: Excellent (ASTM D-3170)

Weatherability: U.V. 7-10 yrs. (ASTM G-53) Operation Temperature Range:-30°- 200°F(-34°- 93°C)

Cut Resistance: Very Good (ASTM D-1044) Salt Spray: Over 15,000 hrs. (ASTM B-117) Permeability: .03 grains/sg.ft. /hr. (ASTM E-96)

VOC lbs. per gallon: 5.4-5.8

Gas Chromatography Test (FID) No evidence of residual vapors

Corrosion Protection from:

Acid Rain Salt Air/Spray Chlorine Muriatic Acid

Uric Acid Amino Acids Hydrogen Sulfide Phosphoric Acid **Ammonia** Sulfuric Acid

ASK FOR COMPETE LIST

Benefits:

- Provides superior resistance to chemicals, corrosion, fading, and chalking
- Extends equipment life, reduces maintenance costs, aids in maintaining operating efficiency

Vinegar

- Protects in virtually any environment
- In the event of damage, can be touched up in the field
- Has little effect on heat transfer (less than ½ of 1%)
- Extends equipment life
- Will NOT chip, crack, powder or flake
- Reduces maintenance costs
- Provides corrosion protection across the entire pH Range (1.0 to 14.0)
- Coating includes a 10-year UV protectant

Coating Application:

This tough, single component air-dry coating provides surface protection in harsh environments where traditional coil coatings fail. Its flexible polyelastomer formula doesn't crack, chip or flake because it expands and contracts with a coil as it heats and cools. Our proprietary coating process has several application methods and can even be Field Applied on location. For best results, we recommend application prior to installation in a controlled environment that will not be affected by adverse weather conditions during application process.

Primary Color: Black Other Colors Available as Special Order

Packaging: 5 Gallon Pails, 50 Gallon Drums, Aerosol Cans

Exclusively Factory-Trained and Licensed Bronz-Glow Applicators ONLY Available To:

Conditions of use: The information and data contained herein, is believed to be reliable and based on our knowledge and experience. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers may be used in combination with our products. Bronz-Glow Technologies does not guarantee the results obtained by applicator or end user. Seller hereby disclaims any implied warranty unless otherwise agreed upon in writing. Buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products whether used alone or in combination with other products. Ever-changing V.O.C. regulations in your area may require you to contact local authorities for proper use and/or disposal of this product. Should you need further assistance, please contact Bronz-Clow Technologies, Inc.