

*It's Going To Rust, So Bring It To Us!*



## Product Data Sheet

# Husky® SPC Clear

## A Versatile Protective Coating

### NSF Certified Product per ANSI 51

#### Coating Characteristics:

Solids: (wt.) 17%

Tensile: 2,600+ psi (ASTM D-638)

Shelf Life: 1 + yrs. @ 77° F (25° C) unopened

Elongation: 350+ % (ASTM D-2370)

Durometer: shore A 70 (ASTM D-2240)

Field Repairable: Yes

Weatherability: U.V. 3-5 yrs. (ASTM G-53)

Operation Temperature Range: -30° - 200°F (-34° - 93°C)

Tear Resistance: .22 (ASTM D-1004)

Salt Spray: Over 10,000 hrs. (ASTM B-117)

VOC: 1 lb. per gallon 5.1-5.5

#### Corrosion Protection from:

Moisture

Alkaline Bases

Salt Water

Animal Fluids

Acidic Bases

Coastal Conditions

U.V. Weathering

Bird Fluids

Salt Air

Abrasion

Scratching

ASK FOR COMPLETE LIST

#### Benefits:

- Provides superior resistance to chemicals, corrosion, fading and chalking
- Reduces maintenance costs
- Protects in any environment
- Safe on all non-food contact surfaces
- Easy to apply: can be sprayed, dipped, rolled or brushed
- Bonds to wood, concrete, glass and plastics with no primer
- Corrosion resistance across the entire pH Range (1.0 to 14.0)
- Protects important information printed on manufacturers labels, i.e. AC cabinets, sprinkler systems, emergency generators, etc.

**Coating Application:** This unique air-dry coating provides tough surface protection in harsh environments where other coatings fail. Husky SPC Clear is used to coat surfaces such as pre-painted metal, galvanized metal, plastic, painted steel, copper and aluminum piping, rubber, along with cement block, masonry, sumps, tower basins and almost any other type of substrate material. Husky SPC becomes impermeable to moisture at 12-15 mils dry thickness. Standard HVAC/R cabinet coating applications are applied at 3-5 mils for general corrosion protection. In addition to corrosion resistance, it can be used in its clear form to protect paper from exterior elements, prevent glass from shattering, and offer scratch resistance to plastics. An ideal coating that allows a manufacturer's colors and product information to be protected and visible without distortion. Apply by spray or dip.

**Packaging:** 5 Gallon Pails, 50 Gallon Drums, Aerosol cans

Conditions of use: The information and data contained herein, is believed to be reliable and based on our knowledge and experience. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers may be used in combination with our products. Bronz-Glow Technologies does not guarantee the results obtained by applicator or end user. Seller hereby disclaims any implied warranty unless otherwise agreed upon in writing. Buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products whether used alone or in combination with other products. Ever-changing V.O.C. regulations in your area may require you to contact local authorities for proper use and/or disposal of this product. Should you need further assistance, please contact Bronz-Glow Technologies, Inc.