

It's Going To Rust, So Bring It To Us!



Product Data Sheet

Husky® Blue Fin

Tough, Flexible Fin Tube Coil Coating Which Doesn't Crack, Chip or Flake
NSF Certified Product per ANSI 51

Corrosion Protection from: Acids, alkalis, acid rain, chlorine fumes, salt air, salt water spray, sulfur water and most other chemical elements.

Coating Recommendation: Bronz-Glow Husky Blue-Fin Coil Coat Protector can effectively be spray applied to the coils of condensing units, refrigeration systems, icemakers and to most any other type of fin/tube or coaxial coil. We recommend coils that are constructed with more than 2 rows of tubing in depth be dip coated. It can also be applied to aluminum, galvanized, copper and/or steel coils.

Benefits:

- Extends equipment life
- Reduces maintenance costs
- Helps prevent "dirty socks syndrome"
- Protects in virtually any corrosive environment
- Aids in maintaining operating efficiency (saves against unnecessary energy loss)
- Easy to apply by spray application
- In the event of damage, can be touched up with a Blue Fin aerosol
- Contains a 10-year Florida sun UV inhibitor for coating preservation

Description: Blue Fin is a unique air dry coating that provides corrosion protection in environments where traditional coil coatings fail. Formulated around a synthetic base, at 1.5 to 2½ mils dry thickness Husky® Blue Fin provides effective corrosion protection in virtually any operating environment.

Coating Characteristics:

Solids: (wt) 17%	Stone Abrasion: Excellent (ADSTM D-3170)
Tensile: 3,740 psi (ASTM D-638)	Weather Ability: U.V. 7-10 yrs. (ASTM G-53)
Finish: semi-gloss	Temperature use range: -30° to 200° F
Shelf Life: 1 + yrs @ 77° F unopened	Cut Resistance: Very Good (ASTM D-1044)
Elongation: 430 % (ASTM D-2370)	Salt Spray: 3,000 hrs (ASTM B-117.85)
Durometer: shore A 70 (ASTM D-2240)	Field Repairable: Yes
VOC lbs. per gallon: 5.1-5.4	Viscosity Range: 80 – 100 K.U. @ 77° F (+/- 2° F)
Gas Chromatography Test (FID) No evidence of residual vapors	

Color: Blue

Coverage Rate: 115 sq.ft. /gal @ 2.5 mils dft (dry film thickness)
225 sq.ft. /gal @ 1.25 mils dft (dry film thickness) *(cover rate may vary based on weather conditions)*

Packaging: 5 gallon pails, 50 gallon drums, aerosol cans